

**AMENDMENTS TO THE CLAIMS**

**This listing of claims will replace all prior versions and listings of claims in the application:**

**LISTING OF CLAIMS:**

1. (currently amended): A vehicle state analyzing method, comprising:

a suspension/chassis setting step for setting an optimum alignment state in a suspension/chassis of a vehicle;

an initialize mode measuring step in which a lateral force ~~between a wheel and~~from all wheels to a vehicle body is measured, by using a force sensor for detecting input of force from ~~the each~~ wheel to the vehicle body, when the vehicle, which is set to an optimum alignment state, is run on a substantially flat road surface as reference under a predetermined condition, and deviation of fluctuation or fluctuation rate of the lateral force with respect to the optimum alignment state is measured;

a monitor mode measuring step in which the lateral force is measured, by using the force sensor, when the vehicle ~~thereafter, which has run a predetermined distance or for a~~predetermined time from a time of performing the initialize mode measuring step, is run on a substantially flat road surface, and deviation of fluctuation or fluctuation rate of the lateral force with respect to the optimum alignment state is measured; and

an analyzing step in which a change of the alignment state of the vehicle is analyzed on the basis of a ratio of the deviation obtained at the monitor mode measuring step and the deviation obtained at the initialize mode measuring step.

RESPONSE TO NOTICE OF NON-COMPLIANT AMENDMENT

U.S. Application No.: 10/551,562

Attorney Docket No.: Q90764

2. (previously presented): The vehicle state analyzing method of claim 1, wherein the deviation of fluctuation or fluctuation rate of the lateral force is measured during normal running of the vehicle.

3. (cancelled).

4. (currently amended): A vehicle state analyzing system for analyzing state of a vehicle having wheels, comprising;

a force sensor for detecting input of force from a wheel to a vehicle body;

initialize mode memory means in which a lateral force ~~between the wheel and~~ from all wheels to the vehicle body is measured, by using the force sensor for detecting input of force from ~~the each~~ wheel to the vehicle body, when the vehicle, which is set to an optimum alignment state, is run during a first period on a substantially flat road surface as reference under a predetermined condition and deviation of fluctuation or fluctuation rate of the lateral force with respect to the optimum alignment state is measured, and stored;

monitor mode memory means in which the lateral force is measured, by using the force sensor, when the vehicle ~~thereafter, which has run a predetermined distance or for a~~ predetermined time from a time of measuring the lateral force by the initialize mode memory means, is run, during a second period after the first period, on the substantially flat road surface and deviation of fluctuation or fluctuation rate of the lateral force with respect to the optimum alignment state is measured, and stored;

RESPONSE TO NOTICE OF NON-COMPLIANT AMENDMENT

U.S. Application No.: 10/551,562

Attorney Docket No.: Q90764

analyzing computation means in which a change of the alignment state of the vehicle is analyzed on the basis of a ratio of the deviation stored in the monitor mode memory means and the deviation stored in the initialize mode memory means; and

information output means for outputting at least one of the information stored in the initialize mode memory means, the information stored in the monitor mode memory means, and a result of the analysis obtained by the analyzing computation means.

5. (previously presented): The vehicle state analyzing system of claim 4, wherein the force sensor is provided in the vehicle, and

the initialize mode memory means, the monitor mode memory means, the analyzing computation means, and the information output means are provided outside the vehicle.

6. (cancelled).

7. (currently amended): A vehicle comprising:

a vehicle state analyzing system mounted thereon, the system comprising:

a force sensor for detecting input of force from a wheel to a vehicle body;

initialize mode memory means in which a lateral force between ~~the wheel and the~~  
from all wheels to the vehicle body is measured, by using the force sensor for detecting  
input of the force from ~~the each~~ wheel to the vehicle body, when the vehicle, which is set  
to an optimum alignment state, is run on a substantially flat road surface as reference

under a predetermined condition and deviation of fluctuation or fluctuation rate of the lateral force with respect to the optimum alignment state is measured, and stored;

monitor mode memory means in which the lateral force is measured, by using the force sensor, when the vehicle ~~thereafter, which has run a predetermined distance or for~~ a predetermined time from a time of measuring the lateral force by the initialize mode memory means, is run on the substantially flat road surface and deviation of fluctuation or fluctuation rate of the lateral force with respect to the optimum alignment state is measured, and stored

analyzing computation means in which a change of the alignment state of the vehicle is analyzed on the basis of a ratio of the deviation stored in the monitor mode memory means and the deviation stored in the initialize mode memory means; and

information output means for outputting at least one of information stored in the initialize mode memory means, information stored in the monitor mode memory means, and a result of the analysis obtained by the analyzing computation means, is mounted.

8. (previously presented): The vehicle of claim 7 further comprising  
display means for displaying the state of the vehicle obtained by the analyzing computation means.

9. (previously presented): The vehicle of claim 7 further comprising  
adjustment means for automatically adjusting alignment of a suspension on the basis of the state of the vehicle analyzed by the analyzing computation means.

10. (currently amended): A vehicle state management system, comprising:

a vehicle state analyzing system for analyzing state of a vehicle having wheels,

comprising:

a force sensor for detecting input of force from a wheel to a vehicle body;

initialize mode memory means in which a lateral force ~~between the wheel~~  
~~and from all wheels to~~ the vehicle body is measured, by using the force sensor for  
detecting input of the force from ~~the each~~ wheel to the vehicle body, when the vehicle,  
which is set to an optimum alignment state, is run on a substantially flat road surface as  
reference under a predetermined condition and a deviation of fluctuation or fluctuation  
rate of the lateral force with respect to the optimum alignment state is measured, and  
stored;

monitor mode memory means in which the lateral force is measured, by using the  
force sensor, when the vehicle, which has run a predetermined distance or for a  
predetermined time from a time measuring the lateral force by the initialize mode  
memory means, thereafter is run on the substantially flat road surface and a deviation of  
fluctuation or fluctuation rate of the lateral force with respect to the optimum alignment  
state is measured, and stored;

analyzing computation means in which a change of the alignment state of the  
vehicle is analyzed on the basis of a ratio of the deviation stored in the monitor mode  
memory means and the deviation stored in the initialize mode memory means; and

RESPONSE TO NOTICE OF NON-COMPLIANT AMENDMENT

U.S. Application No.: 10/551,562

Attorney Docket No.: Q90764

information output means for outputting at least one of information stored in the initialize mode memory means, information stored in the monitor mode memory means, and a result of the analysis obtained by the analyzing computation means; and a vehicle testing apparatus having the substantially flat road surface for running which causes the wheels to be rotated, detecting the state of the vehicle from outside, and being capable of storing the state of the vehicle detected from the outside and the state of the vehicle analyzed by the vehicle state analyzing system.